




Artikelnummer	Beschreibung
N513	Lastbock

Informationen
Baugleich Fibro 2131.15

Bilder

Abmessungen													
Artikel	Nenngröße	Maße in mm									Gewicht kg/pc e	Drehmoment Nm	Reparatur Set
		B	E	A	G	D	F	H	S	SW			
	mm	B	E	A	G	D	F	H	S	SW			
8-211-003G	M8 x 1,25	35	16	30	55	10	85	35	6	13	0,2	30	8-P211-003
8-211-006G	M10 x 1,50	35	21	30	55	10,5	85	36	8	17	0,3	60	8-P211-006
8-211-010G	M12 x 1,75	37	24	33	57	13,5	98	44	8	19	0,5	100	8-P211-010
8-211-012G	M14 x 2,00	37	24	33	57	13,5	98	45	10	22	0,5	120	8-P211-012
8-211-015G	M16 x 2,00	37	29	33	57	13,5	98	46	10	24	0,5	150	8-P211-015
8-211-020G	M18 x 2,00	54	31	50	82	16,5	140	57	12	30	1,3	200	8-P211-020
8-211-025G	M20 x 2,50	54	36	50	82	16,5	140	57	12	30	1,3	250	8-P211-025
8-211-040G	M24 x 3,00	54	41	50	82	16,5	140	59	14	36	1,4	400	8-P211-040
8-211-042G	M27 x 3,00	65	48	60	99	22,5	170	79	17	41	2,8	400	8-P211-042
8-211-050G	M30 x 3,50	65	53	60	99	22,5	170	81	17	46	3,1	500	8-P211-050
8-211-070G	M36 x 4,00	65	60	60	99	22,5	178	88	22	55	3,3	700	8-P211-070
8-211-080G	M36 x 4,00	85	62	77	124	26,5	225	101	22	55	5,8	800	8-P211-080
8-211-100G	M42 x 4,50	85	72	77	124	26,5	225	104	24	65	6,3	1.000	8-P211-100
8-211-150G	M42 x 4,50	104	64	95	158	36	256	112	24	65	10,8	1.500	8-P211-150
8-211-200G	M48 x 5,00	104	65	95	158	36	259	120	27	75	11,6	2.000	8-P211-200

Bestellbeispiel
N513.10.0630 = N513. Gewinde M10, Tragfähigkeit 630 kg

Artikel Article	Gewinde Thread	Tragfähigkeit in to WLL in to									
		 1 0°	 2 0°	 1 90°	 2 90°	 2 0-45°	 2 45-60°	 2 unsymm.	 3-4 0-45°	 3-4 45-60°	 3-4 unsymm.
8-211-003G	M 8	0,30	0,60	0,30	0,60	0,42	0,30	0,30	0,63	0,45	0,30
8-211-006G	M10	0,63	1,26	0,63	1,26	0,88	0,63	0,63	1,32	0,95	0,63
8-211-010G	M12	1,00	2,00	1,00	2,00	1,40	1,00	1,00	2,10	1,50	1,00
8-211-012G	M14	1,20	2,40	1,20	2,40	1,70	1,20	1,20	2,50	1,80	1,20
8-211-015G	M16	1,50	3,00	1,50	3,00	2,10	1,50	1,50	3,10	2,20	1,50
8-211-020G	M18	2,00	4,00	2,00	4,00	2,80	2,00	2,00	4,20	3,00	2,00
8-211-025G	M20	2,50	5,00	2,50	5,00	3,50	2,50	2,50	5,20	3,70	2,50
8-211-040G	M24	4,00	8,00	4,00	8,00	5,60	4,00	4,00	8,40	6,00	4,00
8-211-042G	M27	4,00	8,00	4,00	8,00	5,60	4,00	4,00	8,40	6,00	4,00
8-211-050G	M30	5,00	10,00	5,00	10,00	7,00	5,00	5,00	10,50	7,50	5,00
8-211-070G	M36	7,00	14,00	7,00	14,00	9,80	7,00	7,00	17,70	10,50	7,00
8-211-080G	M36	8,00	16,00	8,00	16,00	11,20	8,00	8,00	16,80	12,00	8,00
8-211-100G	M42	10,00	20,00	10,00	20,00	14,00	10,00	10,00	21,00	15,00	10,00
8-211-150G	M42	15,00	30,00	15,00	30,00	21,00	15,00	15,00	31,50	22,50	15,00
8-211-200G	M48	20,00	40,00	20,00	40,00	28,00	20,00	20,00	42,00	30,00	20,00